

GREENLITE.CA

ACT.NOW.FOREVER

GREENLITEUSA.COM



greenlite™

2017 LIGHTING PRODUCT CATALOG



ACT.NOW.FOREVER



greenlite™

4 - 7 **Our Story**

8 - 9 **Our Technology**

10-19 **LED Bulbs**

20 **LED Fixtures
& Nitelites**

22 - 26 **CFL Bulbs**

We are focused on driving profitable growth by setting the benchmark for energy-efficient lighting innovation, design, quality, and exceptional service.

Our Story

About Us



The time is now for individuals to accept the urgency of climate change and shift their mindsets away from consumption and toward conservation. Greenlite™ promotes the immediate adoption of a more durable future by providing consumers with high-quality low-cost energy-efficient lighting alternatives to collectively reduce our carbon footprint, thereby creating a greener, cleaner home for our families and friends. Greenlite™ is the only provider of innovative, energy-efficient lighting who builds a community around environmental sustainability.

Our quality innovations and service orientation have placed us amongst today's largest North American energy-efficient lighting companies serving both commercial and residential end-users.



Our goal is to stir a community of like-minded people who share our passion and enthusiasm for environmental sustainability thereby creating an emotional connection with a brand that they can believe in.



Our Story

Our Mission



Greenlite's™ mission began twenty years ago with our commitment to supply energy-efficient lighting alternatives to the mainstream. We have successfully made Greenlite™ synonymous with premium CFLs in a variety of wattages, shapes, sizes and colors to replace every incandescent or halogen bulb. Our dedication to product development continues today with market-leading LED technological advancements. We are a leader amongst the few companies worldwide to promote only energy-efficient products. No *ifs, ands, or buts, we walk the walk and talk the talk!*



Our Technology

Our Lights

As an Energy Star® partner since inception, Greenlite™ is committed to providing only the highest quality products in the marketplace.

PRODUCT FEATURES



INSTANT ON



SHATTERPROOF



25,000 H



DIMMABLE



DAMP LOCATION



DUSK TO DAWN



WET LOCATIONS



ENCLOSED FIXTURES

COLOR TEMPERATURE



SOFT WHITE



BRIGHT WHITE



COOL WHITE



DAYLIGHT

PRODUCT CERTIFICATIONS



We understand the importance of creative thinking and are therefore devoted to R&D to successfully develop energy-efficient products for every socket.



Greenlite™ Lighting Corporation is a licensee under the Philip's Licensing Program for LED Luminaires and Retrofits. The program relates to over 200 different innovations resulting in 100 individual patent rights and applications. These innovations encompass the complete range of core technologies that enable Greenlite™ to deliver state-of-the-art LED lighting solutions.



PHILIPS

ACT.NOW.FOREVER



LED bulbs



THE PERFECT LED BULB

... looks just like your standard household bulb.

Traditional
Soft White
Finish

- ✓ Fully Dimmable
- ✓ Omnidirectional Light Everywhere
- ✓ For Use In All Fixtures & Damp Locations

CLASSIC LOOK FLAWLESS LED ILLUMINATION

Available in CLEAR and SOFT WHITE finish:



A19 HOUSEHOLD BULB



CHANDELIER BULB



VANITY BULB



FAN/FRIDGE BULB



AMBER BULB

LED Filament Style Bulbs

Toll Free: 1-877-255-0004
info@greenliteusa.com
www.greenliteusa.com



Chip-On-Glass LED Bulbs



Description	Lumens	Life (Hours)	Incandescent Replacement	Beam Angle°	CCT	
Candle						
*4W Dimmable LEDX Candle E12 Clear	330	15,000	40W	320°	●	☑
4W Dimmable LEDX Candle E12 Frost	300	15,000	40W	320°	●	☑
4W Dimmable LEDX Candle E26 Clear	300	15,000	50W	320°	●	☑
*5W Dimmable LEDX Candle E12 Clear	500	15,000	60W	320°	●	☑
Globe						
*4.5W Dimmable LED G25 Globe Clear	450	15,000	40W	320°	●	☑
A-Type						
*5W Dimmable LEDX A15 Omni Clear	450	15,000	40W	320°	●	☑
*5W Dimmable LEDX A19 Omni Clear	450	15,000	40W	320°	●	☑
*5W Dimmable LEDX A19 Omni Frost	450	15,000	40W	320°	●	☑
*5W Dimmable LEDX A19 Omni Soft White	450	15,000	40W	320°	●	☑
*7W Dimmable LEDX A19 Omni Clear	800	15,000	60W	320°	●	☑
*7W Dimmable LEDX A19 Omni Frost	800	15,000	60W	320°	●	☑
*7W Dimmable LEDX A19 Omni Soft White	800	15,000	60W	320°	●	☑

*Approved for fully enclosed fixtures

● 2700K ○ 3000K ● 4000K ● 5000K



A-type LED General Household



Description	Lumens	Life (Hours)	Incandescent Replacement	CCT	CRI	
15,000 Hours						
6W Dimmable LED A19 Omni	450	15,000	40W	○	82	
*9W Non-Dimmable LED A19 Omni	800	15,000	60W	● ○ ● ●	82	
*9W Dimmable LED A19 Omni	800	15,000	60W	● ○ ●		
25,000 Hours						
*6W Dimmable LED A19 Omni	450	25,000	40W	○	82	
7W Dimmable LED A15 Omni	475	25,000	40W	○	82	
7W Dimmable LED A19	450	25,000	40W	●	82	
7W Non-Dimmable LED A19	450	25,000	40W	○	82	
*7W Dimmable LED A19 Omni AG (Special Dim)	520	25,000	40W	○	84	
*9W Dimmable LED A19 Omni	800	25,000	60W	● ○ ●	82	
*9W Dimmable LED A19 Omni GU24	800	25,000	60W	○	82	
11W Dimmable LED A19 Omni	1100	25,000	75W	○	83	
12W Non-Dimmable LED A21	1200	25,000	100W	●	82	
*12W 3-WAY LED A19 Omni	280/950/1200	25,000	30-70-100W	○	82	JAN 2017
14W 3-WAY LED A21 Omni	450/800/1100	40,000	40-60-75W	○	82	
*15W Dimmable LED A19 Omni	1600	25,000	100W	○ ●	82	
16W 3-WAY LED A21 Omni	360/1240/1650	25,000	30-70-100W	○	82	
18W Dimmable LED A21 Omni	1600	25,000	100W	○	82	

*Approved for fully enclosed fixtures

● 2700K ○ 3000K ● 4000K ● 5000K



ENERGY STAR™ Approved
 ENERGY STAR™ Pending

PAR LED Floodlights



Description	Lumens	Life (Hours)	Incandescent Replacement	Beam Angle°	CCT	CRI	Energy Star
7W Dimmable LED PAR16	500	25,000	75W	38°	○	82	✓
7W Dimmable LED PAR20 FL	500	25,000	50W	40°	● ○ ●	82	✓
7W Dimmable LED PAR20 NFL	500	25,000	50W	25°	● ○ ●	82	✓
11W Dimmable LED PAR30 COB - FL HCRI	800	25,000	75W	40°	● ○ ●	92	✓
11W Dimmable LED PAR30 Short Neck COB - FL HCRI	800	25,000	75W	40°	● ○	92	✓
11W Dimmable LED PAR30 FL	850	25,000	75W	40°	● ○	82	✓
15W Dimmable LED PAR38 FL	1250	25,000	120W	40°	○ ●	82	✓

● 2700K ○ 3000K ● 4000K ● 5000K



✓ ENERGY STAR™ Approved
⌚ ENERGY STAR™ Pending

BR LED Floodlights



Description	Lumens	Life (Hours)	Incandescent Replacement	M.O.L.	Beam Angle°	CCT	CRI	
7W Dimmable LED BR20	500	25,000	50W	3.93"	120°	●	82	✔
7W Dimmable LED BR20 <i>Sleek</i>	550	25,000	50W	3.66"	110°	○	82	✔
8W Dimmable LED BR30 <i>Sleek</i>	650	25,000	65W	5.19"	110°	○	82	✔
8W Dimmable LED BR30	670	25,000	65W	5.16"	106°	○	82	✔
11W Dimmable LED BR30	850	25,000	75W	5.17"	120°	○	82	✔
14W Dimmable LED BR40 <i>Sleek</i>	1100	25,000	85W	6.10"	110°	○	82	✔
17W Dimmable LED BR40	1400	25,000	100W	6.30"	120°	●○	82	✔

● 2700K ○ 3000K ● 4000K ● 5000K



✔ ENERGY STAR™ Approved
⌚ ENERGY STAR™ Pending

MR16 & GU10 LED Spotlights



Description	Lumens	Life (Hours)	Incandescent Replacement	Beam Angle°	Base	M.O.L.	CCT	
4W Non-Dimmable LED MR11 12V	260	25,000	30W	35°	GU4	1.52"	●	
4W Non-Dimmable LED MR16	300	25,000	35W	40°	GU5.3	1.97"	○	
5W Dimmable LED MR16	370	25,000	35W	40°	MR16	1.85"	○	
7W Dimmable LED MR16	520	25,000	50W	40°	GU5.3	1.89"	● ○	
7W Non-Dimmable LED MR16	400	25,000	40W	40°	GU5.3	1.97"	○	
7W Dimmable LED GU10	485	25,000	50W	40°	GU10	2.13"	●	
7W Dimmable LED GU10	520	25,000	50W	40°	GU10	2.17"	○	

● 2700K ○ 3000K ● 4000K ● 5000K



Specialty LED Decorative



2W G4
CLEAR



2.5W G9
CLEAR



5W G16
GLOBE



6W G25
GLOBE



Damp Location



Instant On



Dimmable



Shatterproof

Description	Lumens	Life (Hours)	Incandescent Replacement	Base	CRI	Beam Angle°	CCT	
2W Non Dimmable LED G4 12V	160	15,000	20W	G4	80	180°	○	
2.5W Non Dimmable LED G9 120V	250	15,000	20W	G9	80	180°	○	
5W Dimmable LED G16 Globe	350	40,000	40W	E12	82	240°	○	☑
6W Non-Dimmable LED G25 Globe	450	25,000	40W	E26	82	230°	○	☑

● 2700K ○ 3000K ● 4000K ● 5000K



☑ ENERGY STAR™ Approved

⌚ ENERGY STAR™ Pending

Recessed Cans LED Retrofit Kits



EASY TO INSTALL



- Damp Location
- Instant On
- Dimmable
- Shatterproof


Description	Lumens	Life (Hours)	Incandescent Replacement	CCT	Size	Beam Angle°	CRI	
7W Dimmable LED RC	610	50,000	65W		4"	90°	82	
10W Dimmable LED RC	650	35,000	65W		4"	104°	82	
10W Dimmable LED Square	650	35,000	65W		4"	90°	82	
11W Dimmable LED Gimbal	650	35,000	65W		4"	120°	82	
11W Dimmable LED Gimbal	750	35,000	75W		5"/6"	120°	82	
11W Dimmable LED RC	800	50,000	75W		5"/6"	90°	82	
12W Dimmable LED RC	800	35,000	75W		5"/6"	120°	82	
13W Dimmable LED 5-in-1	800	35,000	80W		4", 5"/6"	100°	82	
23W Dimmable LED Commercial Downlight	1700	35,000	2x18W CFL		6"	90°	82	
24W Non-Dim LED RC (120V-277V)	1500	35,000	150W		8"	90°	82	
33W Dimmable LED Commercial Downlight	2400	35,000	2x26W CFL		8"	90°	82	

2700K 3000K 4000K 5000K



ENERGY STAR™ Approved
 ENERGY STAR™ Pending

Twins/Quads LED PL Lamps



*The lumen performance may vary depending on the type of ballast available, number of lamps and type of fixture.

**Below data is preliminary and may be subject to change.



Description	Lumens	Life (Hours)	CFL PL Replacement	M.O.L	CRI	Beam Angle°	CCT	ENERGY STAR
*4W LED 2-PIN G23 Base 120V-277V	300	50,000	9W	5.82"	80	140°	35K	
*6W LED 2-PIN GX23 Base 120V-277V	520	50,000	13W	5.79"	80	120°	35K	LDL
6W LED 2-PIN GU24 Base 120V-277V	520	50,000	13W in GU24 Base	5.79"	80	120°		
9W LED 4-PIN G24Q Base 120V-277V	950	50,000	18W	5.82"	80	140°	35K	LDL
12W LED 2-PIN G24D Base 120V-277V	1150	50,000	26W	5.82"	80	120°	35K	
12W LED 4-PIN G24Q Base 120V-277V	1150	25,000	13W,18W, 26W	6.77"	80	120°	35K	LDL

*Approved for fully enclosed fixtures

PL BR30 LED PL Lamps



*The lumen performance may vary depending on the type of ballast available, number of lamps and type of fixture.

**Below data is preliminary and may be subject to change.



Description	Lumens	Life (Hours)	CFL PL Replacement	M.O.L	CRI	Beam Angle°	CCT	ENERGY STAR
13W LED BR30 4-PIN G24Q Base Long Neck 120V-277V	1070	50,000	13W,18W, 26W,32W,42W	5.79"	80	120°	35K	LDL

2700K 3000K 35K 3500K 4000K 5000K



ENERGY STAR™ Approved
ENERGY STAR™ Pending

Portables LED Fixtures



Description	Lumens	Life (Hours)	Incandescent Replacement	CCT	
7W Desk Lamp	600	50,000	60W		

2700K 3000K 4000K 5000K

Nitelites LED



SKU	Description	Life	Base	CCT
40351	Diamond Blue: Dawn to Dusk Sensor	Lifetime	Plug-In	
40255	Directional: Swivels 360 Degrees	Lifetime	Plug-In	
91549	Emergency 3-in-1: Emergency Light, Flashlight & Nitelite	Lifetime	Plug-In	

2700K 3000K 4000K 5000K



ENERGY STAR™ Approved
 ENERGY STAR™ Pending

ACT.NOW.FOREVER



CFL bulbs



T2 Spirals

CFL General Household



Item Description	Lumens	Life (Hours)	Incandescent Replacement	M.O.L.	CCT	CRI	ENERGY STAR
13W Ultra-Mini T2 Spiral	900	10,000	60W	3.99"	2700K	82	
13W Ultra-Mini T2 Spiral	900	10,000	60W	3.99"	5000K	82	
*18W Ultra-Mini T2 Spiral	1200	10,000	75W	4.53"	2700K	82	
*18W Ultra-Mini T2 Spiral	1200	15,000	75W	4.53"	4100K	82	
*18W Ultra-Mini T2 Spiral	1250	15,000	75W	4.53"	5000K	82	
*23W Ultra-Mini T2 Spiral	1600	10,000	100W	4.88"	2700K	82	
*23W Ultra-Mini T2 Spiral	1600	10,000	100W	4.88"	4100K	82	
*23W Ultra-Mini T2 Spiral	1600	15,000	100W	4.50"	5000K	82	
*26W Ultra-Mini T2 Spiral	1750	12,000	100W	5.08"	2700K	82	
*26W Ultra-Mini T2 Spiral	1750	15,000	100W	5.08"	4100K	82	
*26W Ultra-Mini T2 Spiral	1750	15,000	100W	5.08"	5000K	82	

*Approved for fully enclosed fixtures



ENERGY STAR™ Approved
 ENERGY STAR™ Pending

T3 & T4 Spirals

CFL High Wattage







Item Description	Lumens	Life (Hours)	Incandescent Replacement	M.O.L.	CCT	CRI
40W High Wattage T3 Spiral	2700	15,000	150W	7.28"	2700K	82
40W High Wattage T3 Spiral	2700	15,000	150W	7.28"	5000K	82
55W High Wattage T4 Spiral	3700	15,000	250W	9.65"	2700K	82
55W High Wattage T4 Spiral	3700	15,000	250W	9.65"	5000K	82
105W High Wattage T5 Spiral	7000	10,000	450W	11.35"	5000K	82
180W High Wattage Spiral T5 E39 Mogul Base	11500	10,000	800W	14.33"	5000K	82



A-type CFL General Household



Item Description	Lumens	Life (Hours)	Incandescent Replacement	M.O.L.	CCT	
9W Covered A-Type	500	8,000	40W	4.21"	2700K	
14W Covered A-Type	800	8,000	60W	4.50"	2700K	
18W Covered A-Type	1100	8,000	75W	5.09"	2700K	
24W Covered A-Type	1600	10,000	100W	5.98"	2700K	



 ENERGY STAR™ Approved
 ENERGY STAR™ Pending

GU24 Base CFL Retrofit Spirals



Item Description	Lumens	Life (Hours)	Incandescent Replacement	M.O.L.	CCT	
9W GU24 Ultra-Mini T2 Spiral	450	10,000	40W	3.31"	2700K	



 ENERGY STAR™ Approved
 ENERGY STAR™ Pending


Twins CFL Tubes



Item Description	Lumens	Life (Hours)	Incandescent Replacement	Base	M.O.L.	CCT
5W Twin Tube 2 Pin	250	15,000	25W	G23	3.22"	3500K
5W Twin Tube 2 Pin	250	15,000	25W	G23	3.22"	5000K
7W Twin Tube 2 Pin	400	15,000	40W	G23	4.4"	2700K
9W Twin Tube 2 Pin	600	15,000	40W	G23	5.7"	2700K
9W Twin Tube 4 pin	600	10,000	40W	2GX7	5.95"	2700K
13W Twin Tube 2 Pin	840	10,000	60W	GX23	6.10"	2700K
13W Twin Tube 2 Pin	840	10,000	60W	GX23	6.10"	4100K

Quads CFL Tubes



Item Description	Lumens	Life (Hours)	Incandescent Replacement	Base	M.O.L.	CCT	
18W Quad 2 pin	1200	10,000	75W	G24d-2	5.10"	2700K	
26W Quad 4 pin	1800	10,000	100W	G24q-3	5.9"	6500K	



Packaging Display Options



GREENLITE.CA

ACT.NOW.FOREVER

GREENLITEUSA.COM



GREENLITE™ USA
10 Corporate Park #100,
Irvine, CA 92606

Tel. 949-261-5300
Fax. 949-261-1798
Toll Free 800-930-2111

info@greenliteusa.com

GREENLITE™ CANADA
115 Brunswick Blvd. #102,
Pointe-Claire, QC H9R 5N2

Tel. 514-695-9090
Fax. 514-695-9093
Toll Free 877-255-0004

info@greenlite.ca

